

# CURRENT MEASUREMENT PROBES

## MR SERIES AC/DC CURRENT PROBES

### MODELS MR415 / 416 / 525 / 526

General Purpose Hall Effect Current Probes for use with DMMs, Data Loggers and Power Analyzers

### SPECIFICATIONS

MODELS	MR415	MR416	MR525	MR526
<b>ELECTRICAL</b>				
Current Range	0.5 to 400A <sub>AC</sub> , 600A <sub>DC</sub>	0.5 to 40A <sub>AC</sub> , 60A <sub>DC</sub> 0.5 to 400A <sub>AC</sub> , 600A <sub>DC</sub>	0.5 to 1000A <sub>AC</sub> , 1400A <sub>DC</sub>	0.5 to 100A <sub>AC</sub> , 150A <sub>DC</sub> 0.5 to 1000A <sub>AC</sub> , 1400A <sub>DC</sub>
Output Signal	1mV/A	10mV/A, 1 mV/A	1mV/A	10mV/A, 1mV/A
Frequency Range	DC to 30kHz (-3dB) (depending of current value)			
Phase Shift At 50/60Hz	≤1.5°@ 400A	≤2.2°@ 40A ≤1.5° @ 400A	≤1.5°@ 800A	≤2°@ 100A ≤1.5° @ 800A
Load Impedance	>1MΩ and ≤100pF			
Overload	3000A <sub>DC</sub> or 1000A <sub>AC</sub> continuous for < 1kHz			
Zero Adjust	Automatic on both ranges			
Power Source	9V Alkaline battery (NEDA 1060A, 6LR61) or 5V DC Micro-USB type B			
Battery Life	50H typical			
Low Battery Indication	Green LED blinking			
Overload Indication	Red LED on when measurement > than selected range			
Output Termination	Double-insulated 5 ft (1.5m) lead with two 4mm safety banana plugs			
<b>MECHANICAL</b>				
Maximum Conductor Size	Cables: (1) 1.18" (30mm) or (2) .94" (24mm) Bus Bar: (1) 1.97 x 0.39" (50 x 10mm) or (2) 1.23 x 0.39" (31.5 x 10mm) or (3) 0.98 x 0.31" (25 x 8mm)		Cables: (1) 1.5" (39mm) or (2) 1" (25.4mm) Bus Bar: (1) 1.97 x 0.49" (50 x 12.5mm) or (2) 0.98 x 0.2" (25 x 5mm); (1) 1.24 x 0.30" (31.5 x 10mm) or (3) 0.98" x 0.31" (25 x 8mm)	
Dimensions (H x W x D)	8.82 x 3.82 x 1.73" (224 x 97 x 44mm)		9.31 x 3.82 x 1.73" (236.5 x 97 x 44mm)	
Weight (with Battery)	0.98lbs (440g)		1.15lbs (520g)	
<b>ENVIRONMENTAL</b>				
Operating Temperature	14° to +131°F (-10 to +55°C)			
Storage Temperature	-40° to +176°F (-40 to +80°C)			
Relative Humidity	Up to 85% @ 35°C			
<b>SAFETY</b>				
Ingress Protection	IP 40			
EMC	EN 61326-1			
Safety Rating	IEC 61010-1, EN 61010-2-32, Pollution Degree 2, 600V CAT III			

Consult factory for NIST Calibration prices

CATALOG NO.	DESCRIPTION
1200.80	AC/DC Current Probe Model MR415 (400A <sub>AC</sub> , 1mV/A & 600A <sub>DC</sub> , 1mV/A, 4mm Banana Plug Lead) - Replaces MR410
1200.82	AC/DC Current Probe Model MR416 (40A <sub>AC</sub> , 60A <sub>DC</sub> , 10mV/A & 400A <sub>AC</sub> , 600A <sub>DC</sub> , 1mV/A, 4mm Banana Plug Lead) - Replaces MR411
1200.81	AC/DC Current Probe Model MR525 (1000A <sub>AC</sub> , 1mV/A & 1400A <sub>DC</sub> , 1mV/A, 4mm Banana Plug Lead) - Replaces MR520
1200.83	AC/DC Current Probe Model MR526 (100A <sub>AC</sub> , 150A <sub>DC</sub> , 10mV/A & 1000A <sub>AC</sub> , 1400A <sub>DC</sub> , 1mV/A, 4mm Banana Plug Lead) - Replaces MR521



### FEATURES

- The jaw shape enables users to clamp on to cables or small bus bars
- Powered by battery or standard external 5V power source via micro-USB connector
- Measures up to 1000A<sub>AC</sub> and 1400A<sub>DC</sub> (model dependent)
- Automatic Zero DC reset function
- Auto Power Off enable/disable function
- Millivolt output compatible with most equipment and instruments
- Battery life up to 50 hours
- Safety rating 600V CATIII



4mm Banana Plug Terminals

# CURRENT MEASUREMENT PROBES

## GENERAL PURPOSE PROBES SELECTION CHART

Series	Model	Ratio	Measurement Range		Output Signal		Phase Shift**	Maximum Conductor Size		Output Connection	Catalog No.
			AC	DC	Current	Voltage		Ø Cable	Bus Bar		
	MN01	1000:1	2 to 150A	–	1mA/A*	–	N/A	0.39" (10mm)	N/A	Leads	2129.17
	MN02	1000:1	50mA to 100A 50mA to 90A	–		–	N/A	0.39" (10mm)	N/A	Leads	2129.20
	MN03	–	2 to 100A	–	–	1mV/A	N/A	0.39" (10mm)	N/A	Leads	2129.18
	MN05	–	5mA to 10A 1 to 100A	–	–	1mV/A 1mV/A	N/A	0.39" (10mm)	N/A	Leads	2129.19
	MN09	–	1 to 150A	–	–	100mVdc/Aac	N/A	0.39" (10mm)	N/A	Leads	2129.21
	MN103	–	1mA to 10A 1 to 100A	–	–	1mV/A 1mV/A	N/A	0.47" (12mm)	N/A	Leads	1031.02
	MN114	–	1mA to 10A	–	–	100mV/A	<8°	0.47" (12mm)	N/A	Leads	2110.71
	MN185	1000:1	50mA to 120A	–	1mA/A	–	<3.5°	0.47" (12mm)	N/A	Jacks	100.185
	MN255	–	0.1 to 24A 0.1 to 240A	–	–	100mV/A 10mV/A	<2.5°	0.78" (19.8mm)	N/A	Leads	2115.81
	MN291	–	0.5 to 240A	–	–	100mVdc/Aac	N/A	0.78" (19.8mm)	N/A	Leads	2115.84
	MN307	–	10mA to 12A	–	–	100mV/A	<2.5°	0.78" (19.8mm)	N/A	Leads	2116.23
	MN312	1000:1	0.1 to 200A	–	1mA/A*	–	<2.5°	0.78" (19.8mm)	N/A	Jacks	2116.24
	MN352	–	0.1 to 150A	–	–	10mV/A	<2.5°	0.78" (19.8mm)	N/A	Jacks	2116.26
	MN353	–		–	–	10mV/A	<2.5°	0.78" (19.8mm)	N/A	Leads	2116.27
	MN375	–	0.1 to 10A	–	–	100mV/A	<1.5°	0.78" (19.8mm)	N/A	Leads	2115.41
	MN379	–	5mA to 6A 0.1 to 120A	–	–	200mV/A 10mV/A		0.78" (19.8mm)	N/A	Leads	2153.01
	SL206	–	10mA to 1.5A 50mA to 60A	10mA to 2A 50mA to 80A	–	1mV/mAac/dc 10mV/Aac/dc	<1°	0.46" (11.8mm)	N/A	Leads	1201.45
	MD301	1000:1	2 to 500A	–	–	1mVdc/Aac	N/A	1.18" (30mm) 2 x 500kc-mil	2.48 x 0.20" (63 x 5mm)	Leads	1201.07

\*Output Protection for open secondary

\*\*Phase shift indicated at maximum rating

Note: Models MN103, MN106, MN114 & MN185 are not CE compliant. MN200 & MN300 series are UL approved except MN379.

Consult factory for NIST Calibration price.

# CURRENT MEASUREMENT PROBES

## GENERAL PURPOSE PROBES SELECTION CHART

SERIES	MODEL	RATIO	MEASUREMENT RANGE		OUTPUT SIGNAL		PHASE SHIFT**	MAXIMUM CONDUCTOR SIZE		OUTPUT CONNECTION	CATALOG NO.
			AC	DC	CURRENT	VOLTAGE		Ø CABLE	BUS BAR		
	MR415	–	0.5 to 400A	0.5 to 600A	–	1mV/A	≤1.5°	1.18" (30mm)	2 bus bar 1.24 x 0.39" (31.5 x 10mm)	5 ft (1.5m) Lead	1200.80
	MR416	–	0.5 to 40A 0.5 to 400A	0.5 to 60A 0.5 to 600A	–	10mV/A 1mV/A	≤2.2° ≤1.5°	1.53" (39mm)	2 bus bar 1.95 x 0.19" (50 x 5mm)	5 ft (1.5m) Lead	1200.81
	MR526	–	0.5 to 100A 0.5 to 1000A	0.5 to 150A 0.5 to 1400A	–	10mV/A 1mV/A	≤2° ≤1.5°	1.53" (39mm)	2 bus bar 1.95 x 0.19" (50 x 5mm)	5 ft (1.5m) Lead	1200.83
	SR601	1000:1	0.1 to 1200A	–	1mA/A*	–	<0.5°	2.05" (52mm)	1.95 x 0.19" (50 x 5mm)	Jacks	2113.43
	SR604	1000:1	0.1 to 1200A	–	1mA/A*	–	<0.5°	2.05" (52mm)	1.95 x 0.19" (50 x 5mm)	Leads	2113.44
	SR651	–	0.1 to 1200A	–	–	1mV/A	<0.5°	2.05" (52mm)	1.95 x 0.19" (50 x 5mm)	Jacks	2113.45
	SR701	1000:1	1mA to 1000A	–	1mA/A*	–	<0.7°	2.05" (52mm)	1.95 x 0.19" (50 x 5mm)	Jacks	2116.29
	SR704	1000:1	1mA to 1000A	–	1mA/A*	–	<0.7°	2.05" (52mm)	1.95 x 0.19" (50 x 5mm)	Leads	2116.30
	SR752	–	0.1 to 1000A	–	–	1mV/A	<0.7°	2.05" (52mm)	1.95 x 0.19" (50 x 5mm)	Leads	2116.32
	SR759	–	1mA to 1A 10mA to 10A 0.1 to 100A 1 to 1000A	–	–	1000mV/A 100mV/A 10mV/A 1mV/A	<1°	2.05" (52mm)	1.95 x 0.19" (50 x 5mm)	Leads	2116.33
	K100	–	0.1mA to 3A	0.05mA to ±4A	–	1mV/mA	N/A	0.18" (4.5 mm)	N/A	Plugs	1200.67
	K110	–	0.1mA to 300mA	0.05mA to ±450mA	–	10mV/mA	N/A		N/A	Plugs	2111.73
	LM102	1000:1	50mA to 200A	–	1mA/A*	–	<3°	0.63" (16 mm)	N/A	Leads	2153.04
	LM103	–	0.1 to 200A	–	–	1mV/A	<3°		N/A	Leads	2153.05

\*Output Protection for open secondary

\*\*Phase shift indicated at maximum rating

Note: All SR probes listed on this chart are UL approved, however not all SR series probes are UL approved; please consult factory. Consult factory for NIST Calibration price.



## OUTPUT TERMINATIONS

### Lead with BNC

Insulated 6.5 ft (2m) coaxial cable with insulated BNC connector rated 600Vrms



### Jacks

Two standard safety banana jacks (4mm)



### Leads

Double/reinforced 5 ft (1.5m) leads with 4mm safety banana plug



### Shrouded Banana Plugs

Two 4mm safety banana plugs; standard ¾" (19mm) spacing



# AMPFLEX® AND MINIFLEX® PROBES - SELECTION CHARTS

SERIES	MODEL	RATIO	MEASUREMENT RANGE	OUTPUT SIGNAL	MAXIMUM CONDUCTOR SIZE	CATALOG NO.
	MF 300-10-2-10-HF	-	30A / 300A	100mV/A, 10mV/A	2.95" (70mm)	2126.84
	MA114	-	3A / 30A / 300A / 3000A	1mV/mA, 100mV/A 10mV/A, 1mV/A	4" (101mm)	2153.41
	300-24-2-10	-	30A / 300A	100mV/A, 10mV/A	7.48" (190mm)	2112.88
	1000-24-1-1	-	1000A	1mV/A	7.48" (190mm)	2112.39
	1000-24-2-1	-	100A / 1000A	10mV/A, 1mV/A	7.48" (190mm)	2112.98
	1000-36-2-1	-	100A / 1000A	10mV/A, 1mV/A	11" (290mm)	2113.00
	3000-24-1-1	-	3000A	1mV/A	7.48" (190mm)	2112.46
	3000-36-1-1	-			11" (290mm)	2112.48
	3000-24-2-1	-	300A / 3000A	10mV/A, 1mV/A	7.48" (190mm)	2113.05
	6000-36-2-0.1	-	600A / 6000A	1mV/A, 0.1mV/A	11" (290mm)	2113.21
	30000-24-2-0.1	-	3000A / 30,000A		7.48" (190mm)	2113.33
	24-3001	-	300A / 3000A <sub>Ac</sub>	10mV/A, 1mV/A	7.48" (190mm)	2120.81

Consult factory for NIST Calibration price

## OSCILLOSCOPE & BNC TERMINATED PROBES

MODEL	MEASUREMENT RANGE		OUTPUT SIGNAL VOLTAGE	PHASE SHIFT*	MAXIMUM CONDUCTOR SIZE		OUTPUT CONNECTION
	AC	DC			Ø CABLE	BUS BAR	
 SL261	100mA to 10A 1 to 100A		100mV/A 10mV/A	<1.5°	0.46" (11.8mm)	N/A	6.5 ft (2m) Lead w/BNC
 MN261	0.1 to 24A 0.5 to 240A			<2.5°	0.78" (19.8mm)		
 SR661	0.1 to 12A 0.1 to 120A 1 to 1200A	-	100mV/A 10mV/A 1mV/A	<1°	2.05" (52mm)	1.96 x 0.19" (50 x 5mm)	
 MN251T MN379T	0.5 to 240A		1mV/A	<2.5°	0.78" (20mm)	0.78" (20mm)	10 ft (3m) Lead w/BNC
	0.005 to 6A		200mV/A	<4°			
	0.1 to 120A		10mV/A	<2.2°			
 MH60	0.5 to 100A	0.5 to 100A	10mV/A	<1°	1.02" (26mm)	N/A	
 MR417	0.5 to 40A 0.5 to 400A	0.5 to 60A 0.5 to 600A	10mV/A 1mV/A	≤2.2° ≤1.5°	1.18" (30mm)	2 bus bar 1.24 x 0.39" (31.5 x 10mm)	6.6 ft (2m) Lead w/BNC
	0.5 to 100A 0.5 to 1000A	0.5 to 150A 0.5 to 1400A		≤2.2° ≤1.5°	1.53" (39mm)	2 bus bar 1.96 x 0.19" (50 x 5mm)	

\*Phase shift indicated at maximum rating. Note: All probes are rated 600V CAT III and CE compliant. Not all models are UL approved; please consult factory. Consult factory for NIST Calibration price.