

**TECHNICAL DATA** 

# Fluke VPS410-II-V ScopeMeter® Voltage Probe Set

### ×

### **Key features**

- Ideal for industrial and electronics applications
- Double insulated, CAT III 1000V / CAT IV 600V rated
- 10:1 voltage ratio and 500 MHz bandwidth
- Available in red, blue, grey, and green

## Product overview: Fluke VPS410-II-V ScopeMeter® Voltage Probe Set

Use the Fluke VPS410-II-V (Green) Voltage Probe with the <u>Fluke 190 Series III</u> and Series II Portable Oscilloscopes or with the <u>MDA-500 Series Motor Drive Analyzers</u>. These double insulated probes offer a 10:1 voltage ratio, and 500 MHz bandwidth making them ideal for industrial, electrical and electronics testing. For smaller size electronic applications consider Fluke <u>VPS510-V Compact Voltage Probes</u>. For test on heavy equipment such as motors and drives, consider the larger and ruggedized Fluke <u>VPS421 Series High Voltage Probes</u>.

### Specifications: Fluke VPS410-II-V ScopeMeter® Voltage Probe Set

Specifications*	
Attenuation	10:1
Bandwidth	500 MHz
Max. input voltage	CAT III 1000V / CAT IV 600V
Max. voltage to ground	CAT III 1000V / CAT IV 600V
Input Resistance	10 ΜΩ
Input Capacitance	11.5 ± 1 pF
Compensation range	1025 pF
Cable Length	1.2 m (3.9 ft)
Safety	IEC / EN 61010-031 UL 61010-031 CSA C22.2 No. 1010.2.031
Max. Altitude	3000 m
Pollution Degree	2
Protection Class	II (double insulation)

\*Specification of probe is valid only when used with Fluke ScopeMeter 190-xxx models and MDA-500 series.



### **Ordering information**

×

#### Fluke VPS410-II-V

Industrial Voltage Probe-set, green, 10:1, 500 MHz

Includes:

- (1) Green voltage probe
- (1) Black hook clip for probe tip
- (1) Black ground lead with mini alligator clip
- (1) Ground spring for probe tip (CAT II 30 V max.)
- (1) Insulation sleeve for probe tip



#### Fluke. Keeping your world up and running.®

Fluke Corporation PO Box 9090, Everett, WA 98206 U.S.A.

#### For more information call:

In the U.S.A. (800) 443-5853 In Canada (800) 36-FLUKE From other countries +1 (425) 446-5500 www.fluke.com ©2024 Fluke Corporation. Specifications subject to change without notice. 05/2024

Modification of this document is not permitted without written permission from Fluke Corporation.