

Part No.

# QTHP-0000

*5kpsi / 35 MPa Hydraulic hand pump, 2 Quick-test outlet ports, 3 ft hose, 1/4" MNPT Process conn.*

5kpsi / 35 MPa Hydraulic hand pump, 2 Quick-test outlet ports, 3 ft hose, 1/4" MNPT Process conn.



QTHP-0000

## Included Items

- Hand Pump - Hydraulic Hand Pump, 5000 psi / 35 MPa (QTHP)
- Process Connection - 1/4" male NPT x male Quick-test, no check-valve, brass (QTHA-2MB0)
- Hose - Quick-test 6900 psi hose, brass hose ends, 3 ft (92 cm) long (QTQT-HOS-3ft)

## Specs/Attributes

Hose 1	Quick-test Hose, Stainless Steel ends, 3ft / 0.9m long
Process Connection	1/4" Male NPT
Reference Connection	None
Weight	50 oz / 3.13 lbs / 1.42 kg
Dimensions	H: 5.7 in (14.48 cm) x W: 6 in (15.24 cm) x D: 8.6 in (21.84 cm)

## Hand Pump QTHP

Materials	Anodized Aluminum, Brass, Stainless Steel
Max Pressure	5000 PSI / 345 bar / 35 MPa
Media Compatibility	Petroleum Based Oil, Water
Seal Materials	Buna-N, Teflon

## Hand Pump QTHP

Fine Adjustment Resolution	0 PSI / 0 mbar / 0.00 kPa
Weight	46.9 oz / 2.93 lbs / 1.33 kg
Dimensions	H: 5.7 in (14.48 cm) x W: 6 in (15.24 cm) x D: 10.6 in (26.92 cm)

## Process Connection QTHA-2MB0

Has Check Valve	No
Materials	Brass
Max Pressure	5000 PSI / 345 bar / 35 MPa
Max Temperature	225 °F / 105 °C
Max Vacuum	0.00 In Hg / 0.00 mm Hg
Min Temperature	0 °F / -18 °C
Seal Materials	Buna-N
Wrench Size	9/16 In 15 mm
Dimensions	H: 1.29 in (3.28 cm) x W: 0.56 in (1.42 cm)

## Hose QTQT-HOS-3ft

Burst Pressure	27000 PSI / 1860 bar / 185 MPa
Color	Silver
Fluid Media	Air, Inert Gas, Natural Gas, Petroleum Based Oil, Water
Inner Diameter	0.08 In / 3.00 mm
Length	3 ft / 92 cm
Materials	Brass
Max Pressure	6900 PSI / 475 bar / 48 MPa
Max Temperature	140 °F / 60 °C
Max Vacuum	0.00 In Hg / 0.00 mm Hg
Min Temperature	-40 °F / -40 °C
Minimum Bend Radius	1.00 In / 26 mm
Outer Diameter	0.20 In / 6.00 mm
Type	QT